

## Installation Instructions: Wall-mounted Perimeter Demarcation Lines

Wall-mounted perimeter demarcation lines are placed on the wall with the **BOTTOM EDGE** of the photoluminescent marking **NO MORE than 4 INCHES ABOVE the finished floor**.

If a 4-inch high wall base is installed in EXISTING construction, that old wall base often is barely hanging on to the wall because its adhesive has dried out. If old wall-base is already half falling off, we recommend the installers use that aged wall-base as alignment and install the photoluminescent marking right above the aged 4-in wall base.

In new construction with freshly applied wall-base or a metal base, installers frequently apply the photoluminescent marking on the base itself.

If neither metal, plastic or rubber base are present, installers mount the photoluminescent marking directly to the wall with the marking bottom edge at or below 4 inches.

### YOUR WALL MARKING OPTIONS:



Wall Tape in 1" or 2"  
164-foot Roll Length



Aluminum Strip with foamy adhesive  
1" x 4 feet

**1. Make sure the installation surface has no paint coming loose. Remove any flaky paint with a scraper and any surface unevenness with sandpaper.**



**2. WATER WET-CLEAN the wall surface with a damp, lint-free microfiber cloth (much better than paper towels) to thoroughly remove any grease, dirt or grime. Discard dirty water and clean with CLEAN water.**



**3. Typically wall surfaces in low location are sufficiently cleaned by water and usually a second wipe with Isopropyl alcohol is not necessary. Installer has to determine the cleanliness on site.**

**→ Prior to the marking installation, wall surface must be grime- and dust-free, dry and clean.**

**5a. Round all Tape ends using scissors or a nail clipper. Press photoluminescent Tape in place. Do NOT pull Tape; instead lay it onto surface without stretching.**

**5b. No need to round Aluminum Strip ends.**



*continued on Page 2*



**6. Remove adhesive-protecting backing withOUT touching adhesive: hold marking along its edges only. Position marking on the wall with the marking bottom edge at or below 4 inches. While the installation shall be continuous, small gaps are acceptable. In corners, do NOT tug the marking in. Instead cut and restart. Do not curve or miter-cut on bends or turning corners. Better to apply short strips on a bend or turn to avoid any wrinkles, as those may come loose. Use a Pressure Roller to apply firm and even pressure onto the Tape to ensure its adhesive backing comes in contact with the entire handrail surface. The pressure roller also helps to squeeze out any bubbles.**

Item-No.: 86-7006



withOUT Pressure Roller: light touch



firmly press-applied = strong contact



Wall Outlining meeting Exit Door Frame



Wall Outlining going across NON-EXIT Doors



**Doors through which occupants must pass do NOT get blocked with a wall-mounted perimeter marking!!**

**Do consult your local AHJ – Authority Having Jurisdiction to install according to YOUR local Code requirements!**

**!! Do NOT use 82-40708L Wall Tape on the Floor !! NOT on Obstacles, such as Pipes !!**