











ETL Intertek Testing listed to UL924 Standard for Emergency Lighting

**Photoluminescent UNFRAMED Aluminum EXIT Sign**  
**50-foot viewing distance**

Item-No:	Description:	Dimensions:
600001	<p>50 foot viewing distance energy-efficient Photoluminescent unframed Aluminum EXIT Sign:</p> <p>Red Aluminum Panel with photoluminescent yellowish letters EXIT (no chevrons)</p> 	8-1/2 inch tall 17 inch wide
600002	<p>&lt;EXIT (The Chevron is surface printed – not peel-and-stick.)</p> 	Each sign has four holes. Hole diameter: 3/16 inch
600003	<p>EXIT&gt; (The Chevron is surface printed – not peel-and-stick.)</p> 	
600004	<p>&lt;EXIT&gt; (The Chevrons are surface printed – not peel-and-stick.)</p> 	
600005	<p>Green Aluminum Panel with photoluminescent yellowish letters EXIT (no chevrons)</p> 	
600006	<p>&lt;EXIT (The Chevron is surface printed – not peel-and-stick.)</p> 	
600007	<p>EXIT&gt; (The Chevron is surface printed – not peel-and-stick.)</p> 	

<p>600008</p>	<p>&lt;EXIT&gt; (The Chevrons are surface printed – not peel-and-stick.)</p>  <p>Also available DOUBLE-sided: Add -DB to Item-Number A double-sided Sign requires One Set of 2 Mounting Clips.</p> <p>OPTIONAL ACCESSORY: Two L-shaped Mounting Clips (screws not included)</p>	
<p>600123</p>	 	<p>1-inch x 1-inch each</p>

## Compliances

### Photoluminescent Exit Sign

- ✓ In compliance with IBC and IFC codes
- ✓ In compliance with NFPA 101-*Life Safety Code*  
Before installation it must be determined that there is a minimum of 5 fc (54 lux) of fluorescent illumination on the face of the sign at all times of building occupancy.
- ✓ OSHA 1910.37 (b)(6) compliant
- ✓ Listed to Standard UL924 by ETL Intertek Testing
- ✓ Four Holes for flat wall mount. OPTIONALLY available if a single-sided sign shall be hung from the ceiling:  
Necessary for a double-sided sign: One Set of 2 L-shaped Mounting Clips (Item-No.: 600123).
- ✓ Listed for high-location and floor-proximity installation = impact resistance tested by ETL!

## Aluminum Exit Sign Benefits

- No energy consumption: no electricity cost; green design
- No maintenance: no bulbs, no battery replacement
- Non-toxic, non-radioactive
- No disposal cost
- Easily movable should egress routing change
- Durable metal with permanent printed design
- Consistent, uniform EXIT legend illumination
- Visible at 50 feet
- Recyclable Aluminum
- LEED points qualified