

IMZI.SA9924 **Luminous Egress-path-marking Systems**

Page Bottom

Luminous Egress-path-marking Systems

See General Information for Luminous Egress-path-marking Systems

AMERICAN PERMALIGHT INC

2531 W 237TH ST TORRANCE, CA 90505 USA SA9924

Permalight[®]

Assembly: 90° angled extruded Aluminum Stair Nosing with 1/2-inch or wider photoluminescent insert, Model(s) CC-NOSING (CC-ALU, CC-FLEX, CC-AST)

Assembly: 90° angled extruded Aluminum Stair Nosing with 1/2-inch or wider photoluminescent insert and black anti-slip insert, Model(s) CC-NOSING (CC-ALU, CC-FLEX, CC-AST)

Assembly: Flat extruded Aluminum Profile for Stair Nosing and flat floor mount with 1/2-inch or wider photoluminescent insert, Model(s) CC-PROFILE (CC-ALU, CC-FLEX, CC-AST)

Assembly: Slanting extruded Aluminum Holder for Walls for 1/2-inch or wider photoluminescent insert strips, Model(s) CC-PROFILE (CC-RIGID, CC-RIGIDX, CC-RIGID-HI, CC-ALU)

Photoluminescent Aluminum strips and signs 1/2-inch or wider, Model(s) CC-ALU (a)

Photoluminescent Anti-Slip Tape strips 1/2-inch or wider, Model(s) CC-AST (a)

Photoluminescent Flexible Vinyl strips and signs 1/2-inch or wider, Model(s) CC-FLEX (a)(b)

Photoluminescent High-Performance Rigid PVC strips and signs 1/2-inch or wider, Model(s) CC-RIGIDHI

Photoluminescent Polyester Thin Film strips and signs 1/2-inch or wider, Model(s) CC-TAPE (b)

Photoluminescent Rigid PVC strips and signs 1/2-inch or wider, Model(s) CC-RIGID, CC-RIGIDX

- (a) Suitable for Wall and Stair Nosing/Floor use.
- (b) Suitable as Obstacle Marking Tape 1" or wider.

Last Updated on 2015-11-24

Questions?

Print this page

Terms of Use

Page Top

@ 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a nonmisleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "@ 2016 UL LLC".